For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

P1-**DL/ P3-**DL PEX Toilet Riser - One-Piece with Compression Sleeve or Insert

Use: For use in potable water distribution systems in accessible locations only

Design Features:

- One-piece construction
- Cut-to-Length for clean, professional installation



Operating Specifications:

Temperature: 40°-180° F

Pressure: 125 PSI maximum

Tubing Diameter: 0.375" OD or 0.50" OD



CONNECTOR MATERIAL SPECIFICATIONS		
Tube	Cross-linked Polyethylene (PEX)	
Compression Sleeve (3/8" OD)	POM	
Compression Insert (1/2" OD)	Stainless steel	

PART DIMENSIONS (Inches)			
Model	DIM. A	DIA. B	
P1-12DL	11.56	.38	
P1-15DL	14.56	.38	
P1-20DL	19.56	.38	

PART DIMENSIONS (Inches)		
Model	DIM. A	DIA. B
P3-15DL	14.56	.50
P3-20DL	19.56	.50

Part Listing:

P1-12DL F	3/8" OD tube x 11-1/2" length, flag label
P1-15DL	3/8" OD tube x 14-1/2" length
P1-20DL	3/8" OD tube x 19-1/2" length
P1-20DL F	3/8" OD tube x 19-1/2" length, flag label
P3-15DL	1/2" OD tube x 14-1/2" length
P3-20DL	1/2" OD tube x 19-1/2" length
P3-20DL F	1/2" OD tube x 19-1/2" length, flag label



Listings & Certifications:

 IAPMO listed to ASME A112.18.1 / CSA B125.1 (including NSF/ANSI 372 and NSF/ANSI/CAN 61)



This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

