

## **COMBINATION BATTERY BACK UP / PRIMARY SUMP PUMP SYSTEM**

### CONSTRUCTION


- Stainless Steel Upper and Lower Float Guard and Float Guide
- Cast Iron Pump Housing/Base with Top Suction Intake to Filter Debris and Minimize Clogging
- ▶ 1-1/2 in. NPT Discharge for Easy Installation and Compliance with Building Codes
- For Use In 14 in. Diameter or Larger Sump Basins
- ▶ 8 ft. SJTW Power Cord


#### **BENEFITS**


- ▶ This system is easy to install in a 16 in basin. Start to finish in about 15 minutes.
- ▶ Removes up to 10,000 on a single battery charge.
- ▶ This pump is assembled in the USA to deliver dependable performance that lasts for years.
- ▶ Protects your basement with hours of pumping power when the electricity goes out.











# JOB-READY, PRE-ASSEMBLED BATTERY BACK UP AND PRIMARY **SUMP PUMP SYSTEM**

MODEL: F33SSn, 1/3 HP | F50SSn, 1/2 HP

#### **PUMP SNAPSHOT**

- ▶ **HP** F33SSn 1/3 HP | F50SSn 1/2 HP | 100 Watt
- ➤ Construction Cast Iron Pump Housing/Base
- ▶ **Switch Type** Integrated Mechanical Float Switch
- ▶ Motor 120 Volt, PSC Oil-Filled Motor
- ▶ Motor 12 Volt DC Back Up Pump
- ▶ Impellers Centrifugal
- ▶ Intakes Top Suction
- ▶ Discharge 1 1/2 In. NPT
- > Submersible Yes
- **F33SSn UPC** 040066218537
- ▶ **F50SSn UPC** 040066218513

#### **SYSTEM SPECIFICATIONS**

- ▶ Length 13 1/2 In.
- **▶ Width** 9 ln.
- ▶ **Height** 15 1/2 ln.
- ▶ Weight 46 Lbs.
- ▶ Power Cord 8 Ft.

#### PERFORMANCE

- ▶ **F33SSn** 1/3 HP Max Flow 77 GPM: 51 GPM @ 10'
- ▶ **F50SSn** 1/2 HP Max Flow 85 GPM: 64 GPM @ 10'

#### FLOW RATES:

MODEL:F33SSn - 1/3 HP	GPM @ 5'	GPM @ 10'	GPM @ 15'	GPM @ 20'
Gal/Min @ 0 MAX Flow 77	64	51	37	20
MODEL:F5OSSn - 1/2 HP	GPM @ 5'	GPM @ 10'	GPM @ 15'	GPM @ 20'
Gal/Min @ 0 MAX Flow 85	75	64	51	34
DC BACK UP PUMP	GPM @ 5'	GPM @ 10'	GPM @ 15'	GPM @ 20'
Gal/Min @ 0 MAX Flow 48	36	25	14	-

#### **3 YEAR LIMITED WARRANTY**

▶ Assembled in USA with Foreign and Domestic Parts





