

Central Air Conditioner/Heat Pump Soft Starters

PRODUCT

SoftStart Home™ soft starters: Modelo SSH6T and Modelo SSH3T

APPLICATION

6-ton (72,000 BTU) and 3-ton (32,000 BTU) central air conditioners/heat pumps

POWER RATING

110VAC (90~135VAC) & 220VAC (187~226VAC), 1 phase

INDOOR/OUTDOOR

Indoor/Outdoor

ENCLOSURE MEDIUM

Module housing sealed in epoxy resin

ADVANTAGES

- Quiet A/C startup - no jarring thump, flickering lights or tripping breaker when A/C starts
- Low-amp startup reduces strain on compressor to help extend A/C life
- Helps start and run A/C on a backup generator
- Starts home A/C with solar energy system without straining battery power supply to other appliances
- Easier and quicker to install than other A/C soft starters

INSTRUCTIONS

Electronic version available at softstarthome.com/support

HAZMAT HAZARD

None

AGENCY LISTINGS



SSH6T



SSH3T

SKU SPECIFIC METRICS

UPC:	SSH6T - 860010067307 SSH3T - 860010067352	Case Dimensions:	SSH6T - 24"L x 14"W x 10"H SSH3T - 18"L x 12"W x 10"H
Unit Dimensions:	SSH6T - 8"H x 3-3/4"W x 2-3/4"D SSH3T - 5-3/4"H x 3"W x 2"D	Case Weight:	SSH6T - 29.5 lbs. SSH3T - 17.2 lbs.
Unit Weight:	SSH6T - 1 lb. 13 oz. SSH3T - 1 lb. 5.2 oz.	Quantity per Case:	10

SoftStart Home™ is a trademark of NetworkRV LLC dba SoftStart, Florida USA