

# ProPEX® Brass Ball Valve

uponor

Submittal Information Revision D: Oct. 19, 2015

## **Project Information**

Joh Name:

JOB Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

## **Technical Data**

Material (body, ball and stem): Forged C37700 Brass Maximum Temperature (no pressure): 200°F (93.3°C)

Maximum Working Pressure: 200 psi Seal: PTFE O-ring: EPDM +FKM

## **Product Information and Application Use**

Uponor ProPEX® Brass Ball Valve is a cost-effective alternative for radiant heating/cooling and hydronic piping applications. 1 Both ends are manufactured with the ProPEX fitting for connections to Uponor PEX pipe. The full-port valves are compatible with propylene glycol mixtures up to 50%. Stem extensions can be installed to accommodate up to 2" of pipe insulation. Note: ProPEX Brass Ball Valves are not approved for potable-water applications.



✓	Description	Part No.	Length	Width	Weight	Cv		
	ProPEX Brass Ball Valve (full port), ½" PEX x ½" PEX	A3205050	2.75"	0.92"	0.36 lbs.	7.0		
	ProPEX Brass Ball Valve (full port), 3/4" PEX x 3/4" PEX	A3207575	3.25"	1.28"	0.52 lbs.	18.0		
	ProPEX Brass Ball Valve (full port), 1" PEX x 1" PEX	A3201010	4.27"	1.81"	1.30 lbs.	29.0		
	ProPEX Brass Ball Valve (full port), 14" PEX x 14" PEX	A3201313	4.75"	1.81"	1.44 lbs.	54.7		
	ProPEX Brass Ball Valve (full port), 1½" PEX x 1½" PEX	A3201515	5.68"	2.07"	2.12 lbs.	68.2		
	ProPEX Brass Ball Valve (full port), 2" PEX x 2" PEX	A3202020	7.125"	2.84"	4.18 lbs.	132.2		
	Stem Extension Kit for ½" and ¾" Valves	F5630001	2.65"	0.906"	0.31 lbs.	N/A		
	Stem Extension Kit for 1" and 11/4" Valves	F5630002	2.65"	1.063"	0.48 lbs.	N/A		
	Stem Extension Kit for 11/2" and 2" Valves	F5620003	2.65"	1.26"	0.57 lbs.	N/A		
T	Tuestallation							

## Installation

Install valve according to local building code. Do not dismantle. Refer to the Uponor Hydronic Piping Design Assistance Manual (HPDAM) or the Uponor Radiant Floor Heating Installation Handbook for additional information.

#### **Standards**

CSA B137.5; ASTM F877; ASTM F1960; NSF359

## **Codes**

IMC; UMC

#### Listings

ANSI/NSF 14; cNSFus-rfh; cQAIus

## **Related Applications**

Radiant Heating and Cooling Systems Snow and Ice Melting Systems Permafrost Protection Systems Turf Conditioning Systems Hydronic Piping Systems

#### **Contact Information**

Uponor, Inc. 5925 148<sup>th</sup> Street West Apple Valley, MN 55124 USA Phone: 800.321.4739 Fax: 952.891.1409 www.uponorpro.com www.uponorengineering.com Uponor Ltd. 2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: 888.994.7726

Fax: 800.638.9517 www.uponorpro.com

www.uponorengineering.com

 $<sup>^1</sup>$ ProPEX $^8$  is a registered trademark of Uponor, Inc. ProPEX $^{\text{TM}}$  is a trademark of Uponor Ltd.