

Product

Condensate Pumps PROCP-16 Series Condensate Pumps

Application

Condensate removal for HVAC/R equipment

Purpose

This product Is designed to automatically evacuate condensate or water discharge from HVACR equipment up to 16' vertically once the condensate in the reservoir reaches a specified level.



AsurityTM PROCP-16 series pumps are an economical alternative based off the proven CP-22 design. PROCP-16 is more compact and designed with a maximum 16 feet of lift. The PROCP-16 series shares many of the great features of the CP-22, including mounting tabs, four inlet holes, metal mounting tabs and a check valve.



Maximum Condensate Temperatures

- Continuous duty 140°F
- Maximum inlet temperature 160°F
- Not suitable for contact with steam or gases that exceed 160°F

Rated Voltage

• 120VAC / 230VAC / 60hHz

Rated Current Draw

- 1.9 Amps (120VAC)
- Amps (230VAC)

Input Type

- USA 3-prong molded plug (120VAC)
- NEMA 6-15 (230VAC)

Maximum Lift Height

PROCP-16 series: 16'

Flow Rate @ Zero Head

PROCP-16: 1.2 gallons per minute

Dimensions

- PROCP-16: 11.8" x 5.9" x 6.7"
- PROCP-16: 5 lbs.

Inlet Height from Base

PROCP-16: 4.4"

Tank Capacity

- PROCP-16: 1/2 gallon
- •

Included Accessories

- Instruction Booklet
- Metal Hang Tabs
- Polyethylene inlet covers (3)
- 4' Remote Shutoff Leads w/insulated terminals

Every AsurityTM condensate pump is computer tested to ensure excellent performance at all pumping levels.



Wiring Color References 120V

- Black Live/Hot
- White Neutral
- Green Ground
- (All installations must conform to local building codes)

230V

- Brown Live/Hot
- Blue Live/Hot
- Green/Yellow Ground
- (All installations must conform to local building codes)

SKU Specific Package Metrics

CATALOG NO.	VOLTS	LIFT	UPC	POWER CORD	ORDER MULTIPLE
PROCP-16	120	16'	095247173006	6"	6
PROCP-16-230	230	16'	095247173013	6"	6