



ULTRACORE ICEMAKER CONNECTOR Specification Sheet			
Part Number	Description	Length	
KDW-912-PP	1/4" Compression x 1/4" Compression	12"	
KDW-924-PP		24"	
KDW-960-PP		60"	
KDW-984-PP		84"	
KDW-996-PP		96"	
KDW-9120-PP		120"	

## **DESIGN FEATURES**

- Exclusive POWR-TIGHT 12-point crimpmany times industry standard
- · Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools required.

## **MATERIAL SPECIFICATIONS**

• Working Pressure: 160 psi

Operating Temperature: 33° F - 140° F
Tubing: Reinforced PVC, NSF 61 Compliant

• Nuts & End Fittings: Nickel-Plated Brass

## **COMPLIANCES/LISTINGS**

- IAPMO Certified
- NSF Compliant
- ASME A112.18.6



3689 Arrowhead Drive, Carson City, NV 89706
Phone (800) 854-3215 Fax (800) 243-1777
E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

AF/S-2015 (04-08) Rev 3

Product Submittal			
Job Name			
Date			
Part Number	Quantity		
Architect			
Contractor			