

## Hef-T-Foot™

### PRODUCT

Hef-T-Foot

### APPLICATION

- HVAC condensing units, air source heat pumps, outdoor equipment

### PURPOSE

Support equipment and enable pipework and cables to run underneath

### FEATURES

#### Hef-T-Foot with Steel Strut

- Stabilization flange flared out from outer walls
- Resistant to impact
- Suitable for drilling for securing equipment

#### Hef-T-Foot Universal

- Gray
- Injection molded high-impact polypropylene
- Unaffected by UV or weather
- Heavily textured surface for non-skid
- Limited Lifetime Warranty

#### Hef-T-Foot Installation Kits

- Mini-Split outdoor unit installation kit includes 2 Hef-T-Feet and installation hardware to attach an outdoor unit.

### MATERIALS

**Rubber** - Compression molded. Working temperature range 14°F to 167°F.

**Strut** - 1.6" x .08" x 0.1" galvanized steel

**Inserts** - M10 (metric course thread) x 20 mm, zinc plated steel, through inserts. Maximum load 55 lbs.

### SPECIFICATIONS

#### Hef-T-Foot with Steel Strut

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-250-S	Hef-T-Foot™ 10" Strut	9.8"	7.3"	3.9"	6.2 lbs.	386 lbs.
FF-400-S	Hef-T-Foot™ 16" Strut	15.7"	7.3"	3.9"	10.1 lbs.	617 lbs.
FF-600-S	Hef-T-Foot™ 24" Strut	23.6"	7.3"	3.9"	16.8 lbs.	926 lbs.
FF-1000-S	Hef-T-Foot™ 39" Strut	39.4"	7.3"	3.9"	26.5 lbs.	1543 lbs.

#### Hef-T-Foot Universal

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-250-UNI	Hef-T-Foot™ 10"	9.84"	7.28"	3.94"	6.2 lbs.	275 lbs.

#### Hef-T-Foot Installation Kits

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	MAX LOAD
FF-400-S-KIT	1 Pair of Hef-T-Foot™ 16" + Installation Hardware	15.7"	7.3"	3.9"	20.2 lbs.	1234 lbs.
FF-450-S-KIT	1 Pair of Hef-T-Foot™ 18" + Installation Hardware	17.7"	6.3"	3.5"	20.8 lbs.	1146 lbs.
FF-600-S-KIT	1 Pair of Hef-T-Foot™ 24" + Installation Hardware	23.6"	7.3"	3.9"	33.6 lbs.	1852 lbs.
FF-1000-S-KIT	1 Pair of Hef-T-Foot™ 39" + Installation Hardware	39.4"	7.3"	3.9"	53.0 lbs.	3086 lbs.



FF-1000-S FF-600-S FF-400-S FF-250-S



FF-600-S-KIT