

GENERAL PURPOSE BRACKET

» 525 SERIES

Support Bracket

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____

SPECIFICATION

Sioux Chief 525 series general purpose, perforated support bracket shall be used where necessary for securing CTS water supply lines vertically or horizontally within a wood or metal 2x4 stud wall. Support bracket is galvanized with pilot holes. Bracket shall resist corrosion. Bracket may be bent if necessary to fit inside stud or joist cavity. Hole schedule on bracket has been designed to align with clamps such as 2-hole galvanized, copper plated pipe straps, plastic pipe or suspension clamps, drop ear 90 fittings or other devices.



525-18

MATERIALS


Brackets: .050 - .070 (15 - 16 gauge)

INSTALLATION

Secure each end of bracket to stud or joist using approved hardware (not included). Install tube or pipe through clamp and attach to bracket.

DIMENSIONS

	525-18	525-20	525-26
A: length	17.88"	19.5"	26"
B: height	0.625"	0.625"	0.625"
C: hole spacing	0.821"	0.821"	0.821"
D: hole diameter	0.188"	0.188"	0.188"



Made in USA

Create Item Number

525-A

e.g. 525-20: 20" support bracket

BRACKET LENGTH A

18 = 18"

20 = 20"

26 = 26"