

ReVent®

Ventilation Fans

80 CFM

ReVent Ventilation Fan

Model - RVS80

Performance - High airflow 80 CFM, low sound 0.7 sones



ReVent with LED Lighting

Model - RVL80

Performance - High airflow 80 CFM, low sound 0.8 sones

LED - Adjustable 2700/3000/3500 /4000/5000K, 1000L, dimmable



ReVent with Humidity Sensing

Model - RVSH80

Performance - High airflow 80 CFM, low sound 0.7 sones

Humidity - Automatically turns fan on when moisture is present and off when dry

Min/Hour Timer - Can be set 0-60 minutes, runs fan for set time every hour



ReVent with LED Lighting and Humidity Sensing

Model - RVLH80

Performance - High airflow 80 CFM, low sound 0.8 sones

LED - Adjustable 2700/3000/3500 /4000/5000K, 1000L, dimmable

Humidity - Automatically turns fan on when moisture is present and off when dry

Min/Hour Timer - Can be set 0-60 minutes, runs fan for set time every hour



SPECIFICATIONS	Models	RVS80, RVL80, RVSH80, RVLH80
	Exhaust Diameter	4 in (10.2 cm)
	Voltage (volts)	120V
	Frequency (hertz)	60Hz
	Power (watts)	19.9 W (non-LED), 20 W (LED)
	Air Flow at 0.1 CW	80 CFM
	Noise (sones)	0.7 Sone (non-LED), 0.8 Sone (LED)
	LED Brightness (lumens)	1000L at 4000K
	LED Color Temp (kelvin)	2700, 3000, 3500, 4000, or 5000K
	LED Power (watts)	13 W
	Shield Size	11 x 11 in (27.9 x 27.9 cm)
Housing Length	8 3/8 in (21.3 cm)	
Housing Width	7 7/8 in (20 cm)	
Housing Depth	4 5/8 in (11.7 cm)	

performance at 4" ducting

Static Pressure (in wg)	Airflow (cfm)	Sound (sones)	Energy (watts)	Duct Size
-------------------------	---------------	---------------	----------------	-----------

RVS80, RVSH80

0.1	80	0.7	19.9	4 in
0.25	63		19.6	4 in

RVL80, RVLH80

0.1	80	0.8	20	4 in
0.25	63		19.5	4 in

Product of GTR Technologies Inc. All rights reserved.
USA and International Patents and Patents Pending
See Patents at www.ReVentfans.com

1-360-876-2974
1420 Lumsden Road
Port Orchard, WA 98367

May be used
to comply with



