


BISMAT® 2000

for metal pipes Ø 2½ - 4"

3/8"

(A 05 210)



Features and benefits

- two-screw clamp
- with BISMAT® quick locking system
- material: steel
- zinc plated
- noise insulating lining, EPDM rubber, black
- age resistant lining
- sound insulating lining according DIN 4109
- complies with Federal Specification WW-H-w171E and A-A-1192A Type 4 and Manufacturers Standardization Society MSS SP-58 and SP-69 type 12
- Plenum rated - tested to ASTM E-84

Part No.	D (mm)	IP (°)	CT (°)	G	B (°)	H (°)	h (°)	b (°)	b x s (mm)	cs	F _{a,z} (lbf)	Pack 1
CR3409105	100 - 105	-	4	3/8"	6.0	5.3	2.9		25 x 2.5	M6	210	25
CR3408070	64 - 70	-	2½	3/8"	4.5	3.9	0.87	0.90	23 x 2.0	M6	210	50
CR3408080	73 - 80	2½	3	3/8"	5.0	4.3	2.4	0.90	23 x 2.0	M6	210	50
CR3408125	122 - 125	-	-	3/8"	6.78	6.58	3.78	1.22	25 x 2.5	M6	-	25
CR3408141	133 - 141	5	-	3/8"	7.36	7.13	4.05	1.22	25 x 2.5	M6	-	25

The max. allowed load (F_{a,z}) is calculated using specific statistical methods related to the breaking load, taking into account a deflection of 1.5 mm or 2% of the maximum nominal clamp diameter.

