

Product

QUIETMINI-M Undermount Pump

Purpose

The Asurity® QUIETMINI-M Undermount Pump is designed to install under wall mounted ductless air conditioners and provide condensate removal utilizing new ultra-quiet pump technology (UQT) along with a stylish sleek design. These tank pumps offer easy installation, hassle free maintenance and ultra-quiet pumping performance. Perfect for those installations in quiet locations - hotels, theaters, bedrooms and meeting rooms.

Features

- Undermount Pump for Ductless Systems
- Ultra Quiet, (21 dBA)
- 2 Year Warranty
- ETL Listed
- Removable Reservoir for Easy Maintenance
- Built-In Safety Overflow Switch
- Quiet. < 19dB(A)
- Max Unit Output 54,000 BTU/h, 16 kW
- Compact Size with Diaphragm Technology

General Specifications

- Power supply: 100-240V / 50/60Hz
- Power consumption: 2.5W
- Max. discharge head: 8m / 26ft
- Max. flow rate: 7.66 GPH (29 LPH)
- Size of outlet port: 6mm (1/4")
- Temperature range: 1~40°C/33~104°F
- Capacity of reservoir: 140mL

Included Accessories

- Bolt, Anchor
- Anti-siphon Valve

General Characteristics

| Part Number | Safety Switch | Power Supply | UPC | Order Multiple |
|-------------|---------------|--------------|---------------|----------------|
| QUIETMINI-M | Yes | 100-240V | 0095247187454 | 10 |

