MERIDIAN DUO

60" x 31" x 21"

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.



MODEL	тми	TUB
Alcove - Right	BMDCRA0RT-XX	BMDCRA0RN-XX
Alcove – Left	BMDCRA0LT-XX	BMDCRA0LN-XX

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$
Jets	36
1 heated backrest	Included
Mia® Control	Included
BU-Touch Control Application BUTOUCH	\$
Geysair®	Included
AromaCloud®* BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$

TUB Soaker	\$
AromaCloud®* BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy

FEATURES				
Installation type	Installation type		Alcove (3 walls)	
No. of bathers	•	Integrated tile flange and skirt with removable panel		
US gallons	35		Included	
Imp. gallons	29	(specify right or left)		
STANDARD COLOR				
White 01 Biscuit 02			Included	

OPTIONS (UPCHARGE APPLICABLE)		
CONTROL (TMU only)		
MiaPlus®** BMIAP1-XX	\$	
WASTE & OVERFLOW 16" x 35" BOVER16-XX		
Chrome 07	\$	
White 01, Biscuit 02	\$	
Brushed Nickel 09, Polished Nickel 10, Oil-rubbed Bronze 11	\$	
IF REQUIRED BY CONSTRUCTION CODE		
16" x 35" Cable driven brass waste & overflow kit BOVERBR	\$	



- * The AromaCloud® is built into the deck (factory installed).
 - ** The MiaPlus® Control is included when purchasing Chromatherapy

TOTAL PRICE



Integrated skirt with removable channel






MERIDIAN DUO

INSTALLATION

(A) When tile flange is added, the AromaCloud® will automatically be installed on the opposite side of the flange.



LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	10 3/8"
В	Outside edge to overflow	5 7/8"
С	Total length	60"
D	Total width	31"
E	Bathing well length	42 3/4"
F	Bathing well width	19 5/16"
G	Deck width	3 1/4"
Н	Deck width at drain end	4"
I	Height from bottom of bath to top deck	21"
J	Tile flange height	1"
K	Height from drain to center of overflow	14 5/8"
L	Maximum water level	13"
М	Slope of backrest	23°

⚠ AromaCloud® position

ⓒ Control position when factory-installed (Mia® or DOT)

Turbine position (TMU)

Indicates heated backrest (TMU)

Indicates WarmTouchShell® position (TUB)

TECHNICAL SPECIFICATIONS			
Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Approx. shipping weight	136 lbs
зарріў гецапса	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Turbine power	550 W
Turbine		Air heater	600 W
	needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	WARRANTY	
Others	The Geysair is located on the same side as the heated backrest. It must NOT be relocated. It must be connected to the hot water supply and be accessible (provide access). Integrated tile flange is included (specify right or left). Integrated skirt with removable panel.	Controls-LED-Geysair*	5 years
Others		Bath & turbine*	20 years
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		* Some restrictions apply www.bainultra.co	om/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.