PRODUCT SHEET

MERIDIAN 6030

60" x 30" x 21"

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.

PRODUCT NO.

MODEL	T№	10	τι	JB
Alcove – Right	BMEBR	ORT-XX	BMEBR	IORN-XX
Alcove – Left	BMEBR	IOLT-XX	BMEBR	IOLN-XX
Drop-in	BMEBR	00T-XX	BMEBR	I00N-XX
THERMOMASSEUR (TI Hydro-thermo massag	\$			
Jets				37
1 heated backrest			Included	
MiaPlus® Control			Included	
BU-Touch Control Applic	ation BUTOU	сн	\$	
Geysair®				Included
AromaCloud®* BAROMAC		\$		
Illuzio Chromatherapy Bo	CHRO6		\$	
TUB Soaker			\$	
			\$	
Soaker				
Soaker AromaCloud®* BAROMAC			\$	
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy BC			\$ \$ \$	with therapy
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy Bo WarmTouchShell® BWTS			\$ \$ \$	with therapy
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy BC WarmTouchShell® BWTS DOT control			\$ \$ \$ Included	with therapy
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy Bo WarmTouchShell® BWTS DOT control FEATURES			\$ \$ \$ Included	
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy Bo WarmTouchShell® BWTS DOT control FEATURES Installation type	CHRO6	Integrated	\$ \$ Included Drop-in & A	
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy BC WarmTouchShell® BWTS DOT control FEATURES Installation type No. of bathers	CHRO6		\$ \$ Included Drop-in & A	Icove (3 walls)
Soaker AromaCloud®* BAROMAC Illuzio Chromatherapy BR WarmTouchShell® BWTS DOT control FEATURES Installation type No. of bathers US gallons	CHRO6		\$ \$ Included Drop-in & A	Icove (3 walls)

OPTIONS (UPCHARGE APPLICABLE)

SKIRT	MULTIFIT BSMUL-XX	SJ-1 BSJ1-XX
White 01, Biscuit 02	\$	\$
WASTE & OVERFLOW 16" x 35" BOVER16-XX		
Chrome 07		\$
White 01, Biscuit 02		\$
Brushed Nickel 09, Polished Nickel 10, Oil-rubbed	Bronze 11	\$
IF REQUIRED BY CONSTRUCTION CODE		
16" x 35" Cable driven brass waste & overflow kit	BOVERBR	\$

* The AromaCloud[®] is built into the deck (factory installed).

\$

TOTAL PRICE

Included

BainUltra⁻

White 01

Biscuit 02







MERIDIAN 6030

INSTALLATION

 Deck modified to host the AromaCloud®.
 When tile flange is added, the AromaCloud® will automatically be installed on the opposite side of the flange.





LETTER	DESCRIPTION	MEASURE
А	Outside edge to center drain	11"
В	Outside edge to overflow	4"
с	Total length	60"
D	Total width	30"
E	Bathing well length	43 5/8"
F	Bathing well width	19 5/8"
G	Deck width	3 1/4"
н	Deck width at drain end	3 1/2"
I	Height from bottom of bath to top deck	20 1/2"
J	Height from bottom of bath to bottom of deck	19"
к	Height from bottom of bath to top of tile flange	21 1/2"
L	Tile flange height	1"
м	Height from drain to center of overflow	16 1/8"
N	Maximum water level	14 3/8"
0	Slope of backrest	24°

AromaCloud[®] position

AromaCloud®

Control position when factory-installed (Mia® or DOT)

Turbine position (TMU)

Indicates heated backrest (TMU)

(indicates WarmTouchShell® position (TUB)

TECHNICAL SPECIFICATIONS

TECHNICAL SP	ECIFICATIONS		
Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template	# 90000053
Turbine li	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Approx. shipping weight	100 lbs
		Turbine power	550 W
		Air heater	600 W
Others	 The Geysair is located on the same side as the heated backrest. It must NOT be relocated. It must be connected to the hot water supply and be accessible (provide access). There is a height difference for the integrated tile flange (see Detail A). Available with or without integrated tile flange (specify right or left) at the same price. 	WARRANTY	
		Controls-LED-Geysair*	5 years
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal,		Bath & turbine*	20 years
provincial/state an	d local building codes and regulations (www.bainultra.com/documentation/documentation).	* Some restrictions apply www.bainul	tra.com/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra* assumes no responsibility for preparatory work done prior to the product being on site.

Copyright © March 2023 | Bains Ultra Inc. All rights reserved.