

# 710CEP-P SERIES POLY-ALLOY (PPSU) COLD EXPANSION PEX FITTING - PLUG

## FEATURES:



- Designed for use in ASTM F1960 Cold Expansion PEX cold and hot water distribution systems
- For use with SDR9 PEX tubing utilizing a PEX expansion ring system
- Larger internal diameter in the fittings providing maximum water flow
- Poly-Alloy material provides resistance to chemicals and in corrosive/aggressive water conditions
- Integral locating tabs to ensure tubing and fitting are installed properly and eliminates faulty connections
- No crimp, expansion connection method provides a positive and leak free connection

## SPECIFICATION:

- Max Pressure Rating: 100 PSI
- Max Temperature Rating: 180°F (82°C)
- Solvay Acudel® PPSU Polyphenylsulfone Polymer

## CERTIFICATION:

- cUPC Standard ASTM F877 / F1960 & CSA B137.5 Certified
- NSF/ANSI Standard 14 & 372 Certified
- Material complies with NSF/ANSI Standard 61



DIMENSIONS						
Part No.	Size	L		W		Weight grams
		inches	mm	inches	mm	
710CEP-P05	1/2"	0.85	21.64	0.84	21.44	3.39
710CEP-P07	3/4"	1.09	27.56	1.09	27.79	6.24
710CEP-P10	1"	1.31	33.35	1.33	33.78	10.96



25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0  
Tel: 800-561-3164

[boshart.com](http://boshart.com) ♦ [blog.boshart.com](http://blog.boshart.com)