

## **COPPER-FLEX™**

**Copper Water Heater Connectors**

*Corrosion is No Match  
for COPPER-FLEX™*

### **Patented Galvanic and Electrolytic Corrosion Protection.**

- Patented internal dielectric insulator sleeve provides superior resistance to galvanic and electrolytic corrosion
- Insulator sleeve effectively isolates dissimilar metals within the water way to eliminate the need for a dielectric union (plastic lined nipple).

### **The Preferred Seal**

- Pliable Nitrile rubber washer requires less torque to seal and is more resilient to rough nipple surfaces.
- Longer connector nuts provide more thread-to-thread contact and a better seal to lined nipples
- Manufactured with solid brass nuts

### **Listed to ASME A112.18.6/CSA B125.6**

- Available in a variety of approved configurations to fit most plumbing system connections



Internal Dielectric Sleeve

Nitrile Rubber Washer



**Compliant**

California (AB1953) and Vermont (S152)

# COPPER-FLEX™ Copper Water Heater Connectors

7/8 IN. O.D. TUBE	Part No.*	Description	Nominal Length/Carton Wt (Lbs)			
			12"	15"	18"	24"
	WB00-N	3/4" F.I.P. X 3/4" F.I.P.	13	15	18	21
	WB03-N	3/4" F.I.P. X 3/4" Nom. Male Sweat (7/8" O.D.)	13	15	18	21
	WB034-N	3/4" F.I.P. X 3/4" Nom. Male/Female Sweat (7/8" I.D.)	13	15	18	21
	WB134-N	1" F.I.P. x 3/4" Nom. Male/Female Sweat	—	—	18	21
	WB234-N	3/4" M.I.P./F.I.P. x 3/4" Nom. Male/Female Sweat (7/8" I.D.)	19	21	22	27
	WB20-N	3/4" M.I.P./F.I.P. x 3/4" F.I.P.	19	21	22	27
	WB23-N	3/4" M.I.P./F.I.P. x 3/4" Nom. Male Sweat (7/8" O.D.)	19	21	22	27

**A Perfect Fit to PEX** Quickly and easily connects directly to PEX pipe.

	WB07	3/4" F.I.P. x 3/4" PEX Brass Barb	—	—	22	27
	WB27	3/4" M.I.P./F.I.P. x 3/4" PEX Brass Barb	—	—	22	27

\*To order, add length to part number (e.g. WB00-18N or WB07-18)

Carton Qty: 25

**⚠ WARNING:** For use with water in readily accessible locations only. DO NOT use with gas – gas will cause corrosion and leakage.

## COPPER-FLEX™ Adaptors

	Part No.	Description	Carton Qty	Carton Wt (Lbs)
	WRU-12-12	3/4-14 Straight Male Pipe Thread x 3/4" M.I.P. Hex Nipple. <b>Brass.</b> Use to Adapt 3/4" F.I.P. Nut to 3/4" M.I.P. on Water Heater Connection.	25	4
	PRB-12-8	3/4-14 Straight Male Pipe Thread x 1/2" F.I.P. Bushing. <b>Brass.</b>	25	1
	WRU-12PX	3/4-14 Straight Male Pipe Thread x 3/4" PEX Barb Adaptor. <b>Brass.</b>	25	3
	WRJ	1.020" O.D. x .687" I.D. x .240" Thick Rubber Washer. For Copper Water Heater Connectors (new style) manufactured after 1990	25	1
	DIS	.940" X .675" I.D. x .218" Thick Rubber Washer. For Copper Water Heater Connectors (old style) manufactured before 1990	5	1



Scan for direct access to BrassCraft Water Heater Connectors

**Brass-Craft Manufacturing Co.**  
39600 Orchard Hill Place  
Novi, Michigan 48375-5331  
TOLL-FREE: (877) 272-7755  
FAX: (248) 305-6011

350 South Edgeware Road  
St. Thomas, Ontario Canada N4P 4C4  
TOLL-FREE: (800) 265-4322  
FAX: (800) 567-9100