







Left Hand Version (4630L) Shown

PRODUCT SPECIFICATIONS:

- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Factory drilled 2-1/2" overflow.
- * Bathwell Dimensions (At Top): W-52-1/4" [1327mm]

D-19" [483mm]

H-15-1/2" [394mm] * Bathwell Dimensions (At Bottom): W-44-1/2" [1130mm] D-17-1/2" [445mm]

- Bathwell Capacity (At Overflow): 42 gal. [159L]
- Water Level (At Overflow): 12" [305mm]
- Available without an overflow model becomes number (4630LM or 4630RM)
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for all other versions of this model.
- AcrylXTM applied acrylic surface

4630L or 4630R

60" [1524mm] Bathtub w/ 18" [457mm] Apron & Let or Right Hand Drain

Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

DWG. # Signatures For Approval: Date: RE4630L or R -CUT Customer: Arch./Engr: By: NMH Quote #: Iob Name: Date: 6/01/2021

IMPOTANT NOTICE