


SECTION "A-A"



Left Hand Version (7936LX) Shown

## PRODUCT SPECIFICATIONS:

- \* Certified to meet CSA B45.5/IAPMO Z124 Standard.
- \* Product has a Class B fire rating as determined by ASTM E-84 test method.
- \* Reinforced & slip resistant floor.
- \* Sufficient drain clearance to accommodate above the floor plumbing.
- \* Integral 1" [25mm] nailing flange.
- \* Spacious, oval shaped bathwell.
- \* Molded shelving.
- \* Factory drilled 2 1/2" [64mm] overflow.
- \* Door Opening: W-56 1/2" [1435mm]

H-57" [1448mm]

\* Bathwell Dimensions (At Top): W-54" [1372mm]

D-26" [660mm]

H-14 1/2" [368mm]

\* Bathwell Dimensions (At Bottom): W-42" [1067mm]

D-21 1/2" [546mm]

- \* Bathwell Capacity (At Overflow): 45 Gal. [170L]
- \* Water Level (At Overflow): 10 3/4" [273mm]
- \* Accepts Clarion Bathware Model IN60C cap (adds 6" [152mm] to the overall height of the unit)
- \* All dimensions +/- 1/2" [12.8mm]
- \* Clarion Bathware reserves the right to change design and/or dimensions.
- \* Dimensions are the same for RE, MP, and all other versions of this product.

## 7936LX or 7936RX

## 60" [1524mm] Tub/Shower w/ Molded Shelving

BATHWARE 44 Amsler Ave. Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

 Signatures For Approval:
 Date:
 Dwg. #

 Customer:
 7936LX or RX

 Arch./Engr:
 -CUT

 Quote #:
 Dwg. By: NMH

 Job Name:
 DATE: 5/25/2022

## \*\*\* IMPORTANT NOTICE \*\*\*