



Submittal Data Sheet

2.0-Ton Slim Duct Built-in Concealed Ceiling Unit
CDXS24LVJU

FEATURES

- Static capability up to 0.16" W.G.
- Rear or bottom return
- Econo Mode for increased energy savings
- LCD wireless remote with backlit display
- 12 year limited parts and compressor warranty with online registration

BENEFITS

- Compact design





Submittal Data Sheet
2.0-Ton Slim Duct Built-in Concealed Ceiling Unit
CDXS24LVJU

PERFORMANCE			
Indoor Unit Model No.	CDXS24LVJU	Indoor Unit Name:	2.0-Ton Slim Duct Built-in Concealed Ceiling Unit
Type:	Ducted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	21,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	
Cooling Input Power (kW):	0.160	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	25,400		
Heating Input Power (kW):	0.16		

INDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L/SL) (CFM):	565/523/477/395
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	23.2
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	5/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-7/8 x 35-7/16 x 24-7/16	Condensate Connection (inch):	25/32
Panel (HxWxD) (in):		Sound Pressure (H/M/L/SL) (dBA):	38/36/34/32
Net Weight (lb):	60	Sound Power Level (dBA):	
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.16 / 0.16

Submittal Data Sheet

2.0-Ton Slim Duct Built-in Concealed Ceiling Unit

CDXS24LVJU

DIMENSIONAL DRAWING

