



Submittal Data Sheet

FDXS12LVJU

FDXS12LVJU

FEATURES

- Intelligent eye occupancy sensor
- Weekly timer for programmable comfort
- Low ambient heat operation down to 0° F
- Low ambient cooling kit available
- 12 year limited parts and compressor warranty with online registration

BENEFITS

- Quiet operation





Submittal Data Sheet

FDXS12LVJU

FDXS12LVJU

PERFORMANCE			
Indoor Unit Model No.	FDXS12LVJU	Indoor Unit Name:	FDXS12LVJU
Type:	Ducted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	11,500	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	
Cooling Input Power (kW):		Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	11,500		
INDOOR UNIT DETAILS			
Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	305/260/235
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	32.0
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	3/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-7/8 x 27-9/16 x 24-7/16	Condensate Connection (inch):	1-1/32
Panel (HxWxD) (in):		Sound Pressure (H/M/L) (dBA):	35/31/31
Net Weight (lb):	47	Sound Power Level (dBA):	51
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.12 / 0.12

Submittal Data Sheet

FDXS12LVJU

FDXS12LVJU

DIMENSIONAL DRAWING

