210 Series

TECTITE® Removable LF Brass Push Ball Valve CxC 3/8" - 2"

SUBMITTAL SHEET







Job Name:			
Job Location:			
Engineer:			
Contractor:			
Tag:			
P0#:			
Rep:			
Wholesale Dist.:			

DESCRIPTION

The TECTITE® 210 Removable Push Ball Valve features a Lead-Free dezincification resistant brass body, Stainless Steel Grab Ring, Stainless Steel ball, a Nylon Separation Ring and an EPDM O-Ring. TECTITE® products are manufactured utilizing proven ASTM materials and standards.

FEATURES

- · Lead-Free Construction
- · No special tools required
- cUPC®, National Plumbing Code of Canada, IPC® Compliant
- · ARRA Compliant
- NSF/ANSI NSF-372 ~ *Lead Free (LF) Compliant.

PERFORMANCE RATING

 TECTITE® products are pressure rated at a maximum of 200 psi (13.7 bar) over a temperature range from 0°F to 250°F

(-17°C to 121°C) for various liquids and gases.

OPTIONS & SIZES

· 3/8", ½", 3/4", 1", 1 1/4", 1 1/2", 2"

APPROVALS


- NSF/ANSI NSF 61 ~ Water Quality; IAPMO File No. 6174
- IGC 157-2013e2; IAPMO File No. 5793

STANDARD MATERIALS LIST

Part Name	Material		
Push Body	UNS C46500 Lead Free Brass		
Grab Ring	316 Stainless Steel		
Support Ring	Nylon		
Ball	Stainless Steel		
0-Ring	NSF Grade EPDM		
Lubrication	Silicone, ANSI/NSF-61 Listed		

DIMENSIONS

Item No.	Description (in.)	A	Height	Width	Depth	Wt. lb.
10155559	210 3/8 CXC	0.94	2.28	5.10	1.00	0.40
10155521	210 1/2 CXC	0.94	2.38	5.17	1.22	0.49
10155523	210 3/4 CXC	1.13	1.70	5.28	1.46	0.73
10155525	210 1 CXC	1.31	3.37	6.20	1.86	1.26
10188118	210 1-1/4 CXC	2.25	3.45	7.25	2.35	2.61
10188121	210 1-1/2 CXC	2.33	4.67	8.99	2.76	4.16
10188123	210 2 CXC	2.75	5.31	9.55	3.26	6.72



^{*} LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.



