



4 In. Square Box, Drawn, 1-1/2 In. Deep with Ten 1/2 In. and Six 3/4 In. KO's, Raised Ground

Catalog #: 192



## FEATURE BENEFIT

Shallow box for installation in walls or ceilings for light fixtures, switches or receptacles

# **PRODUCT FEATURES**

- · Ideal for exposed work applications
- · Combination screw heads allow quick installation
- Drawn construction
- Ten 1/2 In. knockouts and Six 3/4 In. knockouts
- 21.0 Cu. In. capacity
- · Acceptable in 2-hour fire rated walls

### **APPLICATIONS**

- Designed to enclose electrical wiring, switches, receptacles or lighting fixtures
- Constructed from 1/16 In. pre-galvanized steel
- 8-32 cover mounting screws assembled

### CERTIFICATIONS



# **PRODUCT SPECIFICATIONS**

UPC Number: Ea Length/Depth (in.): Ea Width (in.): Ea Height (in.): Wt. Ea. (Lbs.): Package Type: Product UPC-A Labeled: 050169901922 1.563 4.00 4.00 0.660 Loose No

### PACKAGING

HUBBEL

Case I2of5: Standard Carton Qty: Min Order Qty:

COMMERCIAL

CONSTRUCTION

A Division of Hubbell Incorporated (Delaware)

5005069901927 50 50

RACO

574-234-7151

3902 W. Sample St.

South Bend, IN 46619





All RACO single-gang, two-gang, 4 In. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For addtional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com

600V

Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

Revision 1, December 2019



www.hubbell.com/raco/en ©2019 Hubbell. All rights reserved. Information subject to change. Trademarks are property of their respective owners.