

KOHLER® Roughing-In

K-4972-ER
STANWELL™
URINAL

Product Information

Applicable product:	
1-1/4" rear spud urinal	K-4972-ER
Fixture:	
Configuration	Rear spud
Water per flush	1.0 gal (3.8 L)*
Spud inlet size	1-1/4"
Minimum running pressure required	25 psi (172.4 kPa)
* Designed to flush with 1.0 gal (3.8 L) of water when installed with a water-saving flushometer.	
Included components:	
2" outlet spud	10000
1-1/4" inlet spud	18759
Hanger (2 required)	64512
5/8" drain plug	64512

Recommended accessories:	
Touchless DC blowout urinal flushometer – 1.0 gpf (3.8 lpf)	K-10959
Manual blowout urinal flushometer – 1.0 gpf (3.8 lpf)	K-13522

Optional accessories:	
1-1/4" replacement spud	18763

Installation Notes

Install this product according to the installation guide.

Refer to manufacturer's instructions and local codes for flushometer requirements.

Will comply with **ADA** when installed per Section 605 Urinals of the Act.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

*Urinal complies with ADA requirement when rim is mounted no higher than 17" (432 mm) from finished floor.

**Maximum outlet height for ADA compliance.

