



Revel®
Frameless Pivot Shower Door
K-707541-D3

Features

- Vertical handle complements the contemporary style.
- CleanCoat® technology creates a protective barrier that repels water, prevents dirt and minerals from collecting, and makes it easier to remove hard water spots.

Technology

- Frameless, 5/16" (8 mm) thick Frosted tempered glass door.
- Self-closing mechanism offers superior performance and security against water leakage.
- Ultra-low threshold creates easy entry and exit to the showering space.
- Maximum width adjustability.

Installation

- Out-of-plumb adjustability simplifies installation.
- Door can be installed to open to the left or right to suit your bathroom layout.
- Pivot shower door.
- Not for use in hospitality.
- For residential use only.

Recommended Products/Accessories

K-23723 Faucet cleaner

Included Components

Additional Components:

Hardware kit



Codes/Standards

ANSI Z97.1
CPSC 16CFR 1201

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	SHP	Bright Polished Silver
	ABZ	Anodized Dark Bronze
	BNK	Anodized Brushed Nickel


Available Glass Options

Code Description

D3	Frosted
----	---------



Revel®
Frameless Pivot Shower Door
K-707541-D3



*Walk-through

Technical Information

All product dimensions are nominal.

Installation type: For shower base installation
Opening style: Pivot
Opening Width - Min: 39-1/8" (994 mm)
Opening Width - Max: 44" (1118 mm)
Walk-through - Min: 29-3/8" (746 mm)
Walk-through - Max: 34-1/4" (870 mm)
Base-To-Wall Radius – Max: 3/8" (10 mm)
Glass thickness: 5/16" (8 mm)
Glass coating: CleanCoat®

Notes

Install this product according to the installation guide.

Strike jamb is made of clear plastic and may not cover existing shower door holes.

NOTICE: The vertical opening should be a minimum of 74" (1880 mm) to allow clearance for installation.