

Features

- For baths 14" (356 mm) to 21" (533 mm) deep from the center of the bath overflow outlet to the center of the bath drain outlet.
- External 27" (686 mm) length cable.
- No internal linkages to minimize the potential for clogging.
- Includes schedule 40 PVC tubing.

Material

- Metal construction control handle and stopper.

Installation

- Adjustable rotating connection for easy installation.

Recommended Products/Accessories

K-23726 Drain treatment
K-23723 Faucet cleaner



Codes/Standards

ASME A112.18.2/CSA B125.2


KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|---|------|--------------------------------|
|  | CP | Polished Chrome |
|  | SN | Vibrant® Polished Nickel |
|  | AF | Vibrant® French Gold |
|  | PB | Vibrant® Polished Brass |
|  | BN | Vibrant® Brushed Nickel |
|  | BV | Vibrant® Brushed Bronze |
|  | 2BZ | Oil-Rubbed Bronze |
|  | BL | Matte Black |
|  | 2MB | Vibrant® Brushed Moderne Brass |
|  | RGD | Vibrant Rose Gold |
|  | TT | Vibrant Titanium |



Technical Information

All product dimensions are nominal.

Notes

Install this product according to the installation guide.

The combined length of the vertical (supplied) and horizontal (supplied) tubing after being cut for the bath installation must be equal to or less than 25" (635 mm).