

Features

- Two-handle gooseneck bathroom sink faucet.
- 3-11/16" (94 mm) gooseneck spout with rosespray.
- 7-5/16" (186 mm) wall-to-spout outlet.
- 12 gpm (gallons per minute) maximum flow rate.
- Lever handles with red/blue indexing (ADA compliant with correct installation).
- Less drain.
- Adjustable flanges.
- External NPT connections.

Material

- Brass construction.

Installation

- Pairs with the Brockway wall-mounted wash sink.

Recommended Products/Accessories

- K-3200 Utility Sink
- K-3202 Utility Sink
- K-3203 Utility Sink
- K-23723 Faucet cleaner



Codes/Standards



ASME A112.18.1/CSA B125.1
NSF/ANSI 61
NSF/ANSI 372
All applicable US Federal and State material regulations


KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	SR	Vibrant Bright Nickel



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate: 12 gal/min (45.4 l/min)

Pressure: 60 psi (4.1 bar)

Spout:

Spout reach: 3-11/16" (93 mm)

Notes

Install this product according to the installation instructions.