

Features

- ContinuousClean system automatically dispenses cleaning solution with every flush.
- Works with any toilet bowl cleaner tablets. Tablets last for more than one year in ContinuousClean system.
- Revolution 360™ swirl flushing technology generates a powerful swirling motion to keep the bowl cleaner, longer.
- 1.28 gallons per flush (gpf).
- Standard left-hand Polished Chrome trip lever included.
- Supply line not included.
- Combines with the K-20485 bowl to create a complete K-90097 Irvine™ ContinuousClean toilet.

**Technology**

- Adjustment dial lets you set how much cleaning solution is dispensed with each flush.
- Optional: uses two AAA batteries (included) to power the LED system indicator light. System indicator light will notify user when system is working properly and when to replace cleaning agent or batteries.
- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl and trapway to create a strong siphon during flushing.
- AquaPiston® canister allows water to flow out of the tank from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.

Recommended Products/Accessories

K-20485 elongated toilet bowl with skirted trapway

Codes/Standards

ASME A112.19.2/CSA B45.1

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes*Color tiles intended for reference only.*

Color	Code	Description
Light Gray	0	White
Light Tan	96	Biscuit
Light Gray	NY	Dune
Medium Gray	95	Ice™ Grey
Medium Tan	G9	Sandbar
Black	7	Black Black™



Irvine™
ContinuousClean toilet tank
K-90098

No image available.

This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount
Waste Outlet: Floor
Flush type: Gravity siphon jet
Water Consumption
 Full: 1.28 gpf (4.8 lpf)
Rough-in: 12" (305 mm)

Notes

Install this product according to the installation instructions.

Fixture Supply Requirements

Min static pressure: 15 psi (103.4 kPa)
Max static pressure: 80 psi (551.6 kPa)