

Job Name/Location:

Tag #:

Date:

For: File Resubmit
 Approval Other _____

PO No.:

Architect:

GC:

Engr:

Mech:

Rep:

(Company)

(Project Manager)

PMNFP14A1
PI485 for Outdoor Unit



Electrical:

Power Supply	220 VAC (from outdoor unit) 20" Wiring Harness (included)
--------------	--

Surrounding Conditions:

Operating Temperature	-4 - 176 °F
Storage Temperature	-4 - 176 °F
Humidity	0-98% (non-condensing)

Unit Data:

Dimensions	5-3/16" W x 3-5/16" H x 1-3/8" D
Maximum Number of Indoor Units:	64
Maximum Number of Outdoor Units:	1

Standard Features

- PI-485 is a gateway that provides communication between LG Outdoor Units and the LG Central Controllers such as AC Smart IV, ACP IV BACnet, ACP LONworks, etc.

Notes:

- Please contact your LG sales representative for a complete list of compatible DFS units or visit mylghvac.com to view the complete compatibility list.
- Must follow installation instructions in the applicable LG installation manual.

Connectivity:


LG Communications	1 Channel/RS-485 V-Net 32" DFS Wiring Harness (included)
Compatible Models ¹	DFS Single Zone, Multi F, and Multi F MAX

Communications Cabling Specifications (V-Net):

Type	2-conductor, stranded, shielded copper cable/PVC or vinyl jacket
Size	AWG 18-2
Maximum Length	3,280 ft (end-to-end)

AWG - American Wire Gage

Description:



- | | |
|--|----------------------------------|
| 1 LED01G,02G,03G: Communication Status LED | 6 BUS_A: RS-485 (+) Terminal |
| 2 LED1: RS-485 Status LED | 7 BUS_B: RS-485 (-) Terminal |
| 3 CN_PWR: AC 220V Connector | 8 DIP Switch: Product Selection |
| 4 +10V: DC 10V Terminal | 9 CN_OUT: Outdoor Unit Connector |
| 5 GND: Ground | 10 Reset Switch: PI485 (M) Reset |

PMNFP14A1

PI485 for Outdoor Unit




LG

Life's Good

Tag #:

Date:

PO No.:



OR

