

## PRODUCT SUBMITTAL 1307

**Product:** Angle Ball Valve, EVERLOC+™ to Compression  
**Date:** 01 August 2017 (supersedes 01 January 2017)



Article No.	Nominal Size (in.)
418438-001	1/2 x 3/8 Compression

### *TECHNICAL DESCRIPTION*

Specification	ASTM F877 / CSA B137.5
Material	ECO BRASS® (C69300 or CW724R) / valve body and compression are nickel plated
Certifications	cCSAus

### *FUNCTIONAL DESCRIPTION*

EVERLOC+ compression-sleeve valves provide the same reliable connection as other EVERLOC+ compression-sleeve fittings. The maximum temperature and pressure ratings of the EVERLOC+ compression-sleeve fitting system is in accordance with ASTM F877 and CSA B137.5 for SDR9 PEX, see REHAU pipe product submittals for ratings. Installation is performed with EVERLOC+ compression-sleeve tools. Follow all published *REHAU Technical Guidelines*. All EVERLOC+ fittings and sleeves comply with the lead-free (LF) requirements of the U.S. Safe Drinking Water Act.

For updates to this publication, visit [na.rehau.com/resourcecenter](http://na.rehau.com/resourcecenter)

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2017 REHAU