



see what Delta can do™

DELTA® COMMERCIAL THERMOSTATIC ELECTRONIC LAVATORY FAUCET



The DEMD-611LF electronic thermostatic faucet features an integrated thermostatic mixing valve that prevents the water from exceeding 120°F (49°C), satisfying the temperature-limiting requirements of ASSE 1070.

With reliable, hands-free activation, a convenient top mixer, and a 15-second run time, the DEMD-611LF is an ideal handwash faucet for healthcare, education and public facility applications.

The thermostatic mixing valve and supply lines are integrated into the faucet itself. This all-in-one design minimizes installation time and reduces the number of potential leak points.



THERMOSTATIC
CARTRIDGE



ADJUSTABLE
LIMIT STOPS



TEMPERATURE
ADJUSTMENT



DEMD-611LF THERMOSTATIC ELECTRONIC LAVATORY FAUCET



WATER CONTROL FEATURES

- The outlet temperature comfort stop range is adjustable from cold to a maximum of 120°F (49°C), factory set to 105°F (40.5 °C)
- The valve features two “Comfort Limit Stop” pins that can be positioned to control the hot and cold output temperature limits, or to set to a single, fixed outlet temperature
- The valve and electronic components are fully contained within the faucet body, allowing access from above the deck
- A mixing handle allows the user to adjust the temperature
- Factory-set to dispense up to 15 seconds of water

POWER OPTIONS

- Battery operated, battery box and 6 AA batteries included
- A hardwire transformer and converter are available for hardwire installations (order separately)
- A red light on the sensor flashes when the batteries are running low

OTHER SMART FEATURES

- An anti-rotation pin (included) keeps the faucet aligned
- Optional 2.4" round escutcheon ring included
- For retrofit installations, an optional 4" coverplate is available (order separately)
- Using the optional remote control, maintenance personnel can adjust the sensor range and on/off delay times, or activate a line rinse/run for up to 7 minutes (order separately)



THERMOSTATIC ELECTRONIC LAVATORY FAUCET

DEMD-611LF – 0.66 gpm (2.5 L/min)
0.17 gal/cycle (0.64 L/cycle)*
DEMD-611-10LF – 1.0 gpm (3.8 L/min)
0.25 gal/cycle (0.94 L/cycle)*



OPTIONAL REMOTE CONTROL
060967A



DEMD PLUG-IN POWER SUPPLY
060958A
For plug-in applications



OPTIONAL 4" COVERPLATE
060585A

5-year limited warranty.

IAPMO certified.

Complies to ASME A112.18.1/
CSA.B125.1, CSA B125.3 and
ASSE 1070.

*Based on 15 second run time



see what Delta can do™

deltacommercialfaucets.ca
800.567.3300
©2015 Masco Canada Limited
MKT-15-084E

For hardwire applications, order both of the following:



20VA TRANSFORMER
060704A – 120VAC to 24VAC



PLUS
DEMD CONVERTER
060974A – 24VAC to 9VDC