

# Cimarron® Comfort Height®

Elongated chair height toilet bowl **K-5309** 

#### **Features**

- Elongated bowl offers added room and comfort.
- Skirted trapway simplifies cleaning.
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults.
- 2-1/8" (54 mm) fully-glazed trapway.
- Patented ReadyLock™ installation system is a simple solution for skirted toilets that saves time, hassle, and eliminates the need to drill into the floor for a standard 12" (305 mm) roughin.
- Combines with the K-4369/4369-RA tank to create a complete K-5310/5310-RA Cimarron toilet.
- Coordinates with other products in the Cimarron collection.

## Installation

- Standard 12-inch rough-in (10- and 14-inch rough-in kits also available).
- Seat and supply line sold separately.

# **Recommended Products/Accessories**

K-4369 Toilet tank, 1.28 gpf K-23726 Drain treatment

## **Included Components**

Additional Components:

Floor Mounting Kit



## Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC

# **KOHLER® Toilets and Seats Limited Warranty**

See website for detailed warranty information.

# **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
7	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	7	Black Black™





# Cimarron® Comfort Height®

Elongated chair height toilet bowl **K-5309** 

No image available. This product is a component and not intended to be a standalone installation.

## **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece

Trap passageway: 2-1/8" (54 mm)

Rough-in: 12" (305 mm)

## **Notes**

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

