

HEAT PUMP OUTDOOR UNITS

7SCP18V

Cold Climate | Variable Capacity | Side Discharge | R-454B | 60Hz

RESIDENTIAL PRODUCT SPECIFICATIONS

SEER2 up to 19.0
HSPF2 up to 10.0
2 to 5 Tons




7SCP18V36
(7SCP18V24 not shown)



7SCP18V60



MODEL NUMBER IDENTIFICATION



CONTENTS

MODEL NUMBER IDENTIFICATION	1
APPROVALS AND WARRANTY	2
FEATURES	2
SPECIFICATIONS	5
DIMENSIONS	6
INSTALLATION CLEARANCES	9
TXV SUBSTITUTION - R-454B	10
TXV USAGE	10

APPROVALS AND WARRANTY

APPROVALS

- AHRI Certified to AHRI Standard 210/240-2023
- For AHRI Certified system match-ups and expanded ratings, visit www.alliedratings.com
- Omniduct® certified
- Sound rated to AHRI Standard 270-2008 test conditions
- Rated According to U.S. Department of Energy (DOE) test procedures
- Units and components UL, NEC, and CEC bonded for grounding to meet safety standards for servicing
- ETL certified (U.S. and Canada)
- ISO 9001 Registered Manufacturing Quality System
- ENERGY STAR® Cold Climate certified

WARRANTY

- 10-years limited warranty on all parts, extended warranty available.
- Coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty).
- Warranty must be registered online within 60 days of installation to qualify for 10-year coverage.
- Unregistered equipment defaults to 5-year coverage.
- See full warranty at www.alliedair.com for terms, conditions, and exclusions.

FEATURES

APPLICATIONS

- 2 through 5 ton
- Sound levels as low as 54 dBA
- Single phase power supply (208/230V)
- Side discharge air
- Units shipped completely factory assembled, internally piped, and wired

NOTE - The 7SCP18V model can be configured to operate as a 4 or 5 ton unit.

NOTE - When heat pumps are used with gas furnaces, a dual-fuel compatible thermostat or a zone control system with dual-fuel capabilities must be used (order separately)

NOTE - Installer must set outdoor unit, connect refrigerant lines and make electrical connections to complete job.

REFRIGERATION SYSTEM

R-454B Refrigerant

- Low GWP (Global Warming Potential)
- Zero ODP (Ozone Depletion Potential)
- Low Toxicity/Lower Flammability - A2L

Outdoor Coil

- Aluminum fins fitted to copper tubes

Outdoor Fan

- Direct drive fan moves large air volumes uniformly through entire outdoor coil for high refrigeration capacity
- Fan guard provided

Refrigerant Line Connections, Service Valve

- Flare connection lines are located on side of unit cabinet
- Fully serviceable brass service valve prevents corrosion and provides access to refrigerant system
- Suction and liquid extension pipes furnished

FEATURES

INDOOR REFRIGERANT DETECTION SYSTEM (RDS)

- Complies with UL 60335-2-40 approved standard
- Required for all systems using R-454B refrigerant
- Factory or field installed on all indoor units
- Consists of a RDS refrigerant detection sensor and a mitigation control in the indoor unit
- Ensures safe operation for systems equipped with R-454B refrigerant
- Indoor sensor will detect any R-454B refrigerant
- If R-454B refrigerant is detected, the refrigerant detection system will stop compressor operation and operate the blower to reduce concentrations in the conditioned space
- Once safe levels are reached the HVAC system will resume normal operation
- Refer to indoor unit Product Specifications documents for additional details

COMPRESSOR

Variable Frequency Rotary Compressor

- Compressor features high efficiency operation
- Balanced for reduced vibration and quiet operation
- Brushless DC motor uses powerful Neodymium magnets, which are approximately 15-20 times stronger than ferrite magnets used in conventional AC compressors

Compressor Crankcase Heater

- Protects against liquid refrigerant migration that can occur during low ambient operation

CONTROLS

DC Inverter Control

- Provides continuous operation, while adjusting capacity according to room temperature
- The accurate sensing of cooling loads prevents frequent changes in capacity and ensures efficient, economical operation

Inverter Module Protection

- Protects against differences in current, voltage and temperature
- Displays code on the indoor unit indicating a need for servicing

Outdoor Unit Microprocessor

- Electronic expansion valve control
- Automatic compressor timed-off protection (3 minutes)
- Temperature sensor
- LEDs on control display error codes and assist in troubleshooting
- 4-Way reversing valve control

Electronic Expansion Valve

- Furnished on all models for heating control

Compressor Overcurrent Protection

- Overcurrent protection can result due to any of the following:
 - Ambient temperature is too high
 - Locked rotor on the compressor
 - Outdoor air is blocked or restricted

Condenser High Temperature Protection

- Condenser high temperature can occur due to any of the following conditions:
 - High outdoor ambient
 - Outdoor fan blocked
 - Outdoor coil blocked
- The outdoor coil thermistor continuously monitors the temperature and communicates with the microprocessor
- Depending on the temperature measured, the compressor will be allowed to increase the frequency if needed to meet the load or is forced to run at the current or reduced frequency
- If the temperature becomes excessively high the compressor will be de-energized

Compressor Discharge Temperature Protection

- The compressor discharge line thermistor continuously monitors the temperature and communicates with the microprocessor
- Depending on the temperature measured, the compressor will be allowed to increase the frequency to meet the load or is forced to run at the current or reduced frequency
- If the temperature becomes excessively high, the compressor will be de-energized

FEATURES

Voltage Protection

- Protects unit from low or high voltage fluctuations

Terminal Strip

- Furnished for easy wiring connections

Defrost Control

- Defrost cycle is automatically enabled if there is a build-up of frost on the outdoor coil
- Outdoor fan operation is terminated during the defrost cycle
- Indoor fan changes to ultra low speed during the defrost cycle to help bring warm refrigerant back to the outdoor coil to assist during defrost operation
- Defrost LED is lit on the indoor unit panel on the front cover during a defrost cycle

Reversing Valve

- 4-way interchange reversing valve effects a rapid change in direction of refrigerant flow resulting in quick changeover from cooling to heating and vice versa
- Valve operates on pressure differential between outdoor unit and indoor unit of the system

Optional Accessories

E30 Smart Wi-Fi Thermostat

CABINET

- Constructed of heavy gauge steel
- Tabs on unit base allow secure mounting to slab
- Condensate drain outlets furnished on unit base

NOTE - Drain must be field furnished.

- Pan heater prevents ice build-up in the bottom of the unit during heating operation
- Access cover for power and control wiring connections
- Access cover for service valves
- Rubber dampening pads (4)

SPECIFICATIONS

Size	024	036	060
Nominal Size - Tons	2	3	4/5
Ambient Temperature Range - °F	Cooling	5°F - 115°F	5°F - 115°F
	Heating	-22°F - 86°F	-22°F - 86°F
Sound Data (low)	dBA	54	57
Refrigerant	¹ Charge furnished (R-454B)	3 lbs. 9 oz.	5 lbs. 9 oz.
	Maximum line length with furnished charge - ft.	15	15
	Additional charge required per ft. - oz.	0.55	0.55
Compressor	Number and Type	(1) Variable Rotary	(1) Variable Rotary
	Refrigerant oil type	HAF68D1C	RM68EH
	Refrigerant oil charge - oz.	30.4	29.4
Connections	Liquid OD (flare) - in.	3/8	3/8
	² Suction OD (flare) - in.	5/8	3/4
	Refrigerant line size - Liquid - in.	3/8 - same size as unit connection	
	² Refrigerant line size - Suction - in.	3/4	7/8
	Maximum line length - ft.	150	150
Maximum height difference between indoor and outdoor unit - ft.		50	50
Outdoor Coil	Net face area - ft. ²	7.19	9.61
	Tube diameter - mm	7	7
	Rows	3	3
	Fins - in.	18	18
	Fin type	Hydrophilic aluminum	
	Tube type	Inner Grooved Copper Tube	
Outdoor Fan(s)	HP	1/4	1/4
	(Number) Diameter - in.	(1) 22	(1) 25
	Blades	3	3
	Total air volume - cfm	3000	3330
	Rpm	680	700
	Watts	160	200
Shipping/Net Data - lbs.		137 / 161	157 / 190
ELECTRICAL DATA			
Compressor	Line voltage data (Volts-Phase-Hz)	208/230-1-60	208/230-1-60
	³ Maximum Overcurrent Protection (MOCP) amps	30	35
	⁴ Minimum circuit ampacity (MCA)	21	24
Fan Motor	Rated Load Amps	14.5	16.5
	Rated load amps	1.2	1.5
Shipping/Net Data - lbs.			

NOTE - Extremes of operating range are plus and minus 10% of line voltage.

¹ Refrigerant charge sufficient for 15 ft. length of refrigerant lines. For longer line set requirements see the Installation Instructions for information about line set length and additional refrigerant charge required.

² Line set sizes for Suction Line (unit to line set):

024 - 5/8 to 3/4 in.

036 - 3/4 to 7/8 in.


060 - 3/4 to 7/8 in.

³ HACR type circuit breaker or fuse.


⁴ Refer to National or Canadian Electrical Code manual to determine wire, fuse and disconnect size requirements.

DIMENSIONS


7SCP18V24



FRONT VIEW





SIDE VIEW



BOTTOM VIEW

DIMENSIONS


7SCP18V36




BOTTOM VIEW

DIMENSIONS


7SCP18V60



FRONT VIEW




SIDE VIEW



BOTTOM VIEW

INSTALLATION CLEARANCES

SINGLE UNIT INSTALLATION



NOTE - Top and two sides of unit must be exposed to open space,
Any barriers on one side of the front or back must be lower than unit height.

MINIMUM CLEARANCES

Control Box (Service)	30 in. (762 mm)
Discharge Air	14 in. (356 mm)
Space Between Units	4 in. (102 mm)
Space From Wall	4 in. (102 mm)

NOTE - Maximum soffit overhang is 36 inch (914 mm).

At least one side should be unobstructed by a wall or other barrier.

TXV USAGE

All Allied coils and air handlers are shipped with a factory installed TXV. In most cases, no substitution is needed. If a different size TXV is required, it will be listed in the "TXV SUBSTITUTION" table by size. The correct TXV must be ordered separately and field installed.

Size	Order Number
024	26Z70
036	26Z70
048	26Z71
060	26Z72

AHRI STANDARD 210/240-2023

Standard Ratings relating to cooling or heating capacities shall be net values, including the effects of circulating-fan heat, but not including supplementary electric heat. Power input used for calculating efficiency shall be the Total Power.

Standard Ratings of units which do not have indoor air-circulating fans furnished as part of the model, i.e., Coil-only System, shall be established by subtracting from the total cooling capacity 1,505 Btu/h per 1,000 SCFM, and by adding the same amount to the heating capacity for non-mobile-home, non-Space Constrained units. Total Power for both heating and cooling shall be increased by 441 W per 1,000 SCFM of indoor air circulated.

TXV SUBSTITUTION - R-454B

A general guide for replacing the factory installed R-454B TXV if the indoor unit (coil/air handler) is larger or smaller than the outdoor unit.

Outdoor Unit		Indoor Unit		Indoor TXV Furnished	Indoor TXV Replacement
Size	Tons	Size	Tons		
024	2	42	3.5	26Z71	26Z70
024	2	48	4	26Z71	26Z70
024	2	49	4	26Z71	26Z70
024	2	50/60	4/5	26Z71	26Z70
024	2	51/61	4/5	26Z71	26Z70
024	2	60	5	26Z72	26Z70
036	3	42	3.5	26Z71	26Z70
036	3	48	4	26Z71	26Z70
036	3	49	4	26Z71	26Z70
036	3	50/60	4/5	26Z71	26Z70
036	3	51/61	4/5	26Z71	26Z70
036	3	60	5	26Z72	26Z70
048	4	30/36	2.5/3	26Z70	26Z71
048	4	36	3	26Z70	26Z71
048	4	60	5	26Z72	26Z71
060	5	50/60	4/5	26Z71	26Z72
060	5	51/61	4/5	26Z71	26Z72

TXV Ranges:

- 26Z70** - 1.5 to 3 ton systems - Use on 3 ton (036) and lower systems.
- 26Z71** - 3.5-4 ton systems - Use on 4 ton (048) and down to 3.5 ton (042) systems.
- 26Z72** - 5 ton systems - Use on 5 ton (060) systems only.



Visit us at www.alliedair.com

Contact us at 1-800-448-5872

NOTE - Due to our ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

©2025 Allied Air Enterprises.