



Toilet wall-mounted	Dimension	Weight	Order number
washdown model, suitable for SensoWash Starck, Durafix included, cUPC® listed*	(		
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze provides almost indefinite effectiveness)	e that		
Variant			
<b>1.6/0.8 gpf</b>	14 1/8" x 24 3/8" Inch	64 lb	22260992
<b>1.6/0.8 gpf</b>	14 1/8" x 24 3/8" Inch	64 lb	22260992
Infobox			
Durafix for concealed installation is included, * Complies ASME A112.19.14, For suitable SensoWash® shower-toile carrier and actuator plate required for installation / Refe installed with a seat height of 17" - 19" from the finished	et seats, please see matrix on p r to page XXX, Wall-mounted to	age xxx, In-wall tar ilet is ADA complia	nk &
Sigma 01 flush plate, dual flush for toilets, White	9 5/8" x 6 1/2" Inch		115770
Geberit in-wall tank and carrier for toilets	19 3/4" x 3 1/8" Inch	37.5 lb	111798
Geberit in-wall tank and carrier for toilets	19 3/4" x 5 1/2" Inch	40.8 lb	111335
Noise reduction gasket for wall-mounted toilet		0.7 lb	005020
Suitable products			
Toilet seat and cover elongated, hinges stainless steel, removable, with slow close,			006339



## **Starck 3 Toilet wall-mounted & # 222609..92 / 222609..92**

|< 14 1/8" Inch >|

SensoWash® Starck shower-toilet seat for Starck 2, Starck 3 and Darling New* Rear-, Lady- and Comfortwash, individual adjustment of water-, air- and seat surface temperature as well as nozzle position and jet strength, power actuated lid and seat, night light, 2 individually programmable user profiles, remote control included, self-cleaning wand, on / off-button, Quick release: easy seat unit removal and attachment, 14 5/8" x 20 1/4" Inch	610000
Toilet seat ring elongated, open front, hinges plastic, without slow close,	006431
Toilet seat ring elongated, open front, hinges plastic, with slow close,	006439
Toilet seat and cover elongated, hinges stainless steel, without slow close,	006332

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.