

EZ-IN™ MINI SPLIT

EZ-IN™ SHIELDED MINI-SPLIT CABLE



Temperature Rating: 90°C (Dry) and 75°C (Wet), 600V, Rated Sunlight Resistant and Direct Burial

APPLICATION

Southwire's shielded armored mini-split cable can be installed in accordance with The National Electrical Code for HVAC applications without the use of conduit and may be installed indoors or outdoors in wet locations.

TOOLS

- Using appropriate Southwire tools for mini-split installations to reduce the chance of damage to internal wires See Tool Kit

CONSTRUCTION

- Conductor(s): Stranded, bare copper Class B, Soft Drawn Annealed Bare Copper per ASTM B3 and B8
- Insulation: Polyvinyl Chloride (PVC)/Nylon
- Shield: Aluminum foil tape shield with 18 AWG tinned copper drain wire
- Armoring: Aluminum Interlocked Armor (AIA)
- Jacket: Black, PVC

SPECIFICATIONS:

- ASTM B3, B8
- UL 83 - Thermoplastic Insulated Wires and Cables
- UL 1569 - Metal-Clad Cables
- NFPA 70
- RoHS-3



STOCK #	DESCRIPTION	AWG	SOLID STRANDED	#COND	JACKET COLOR	CONDUCTOR COLOR	OVERALL DIAMETER (MILS)	NET WEIGHT (LBS/1000 FT)
593512	EZIN14/4STR DW AL SHD 600V AA JT	14	Stranded	4	Black	Black, Red, White, Green	587	163

HVAC TSTAT | EZ-IN™ MINI SPLIT