

Job Name/Location:

Tag No.:

Date:

For: File Resubmit

PO No.:

Approval Other\_\_\_\_\_

Architect:

GC:

Engr:

Mech:

Rep:

(Company)

(Project Manager)

PRARH0

Auxiliary Heater Relay Kit for Gen 2 Multi V, SZ, and Multi F IDUs



#### Electrical:

Power Supply 12VDC (From Indoor Unit)

#### Operation Conditions:

Operating Temperature 14 to 158°F  
Storage Temperature -4 to +176°F  
Humidity 0 – 98% Non-Condensing

#### Unit Data:

Dimensions (W x H x D, in.) 7-9/32 x 3-13/32 x 2-9/32  
Contact Rating 3A @ 24VAC

#### Connectivity:

LG Communications V-Net  
Cable 30" Wiring Harness (included)

#### Standard Features:

- Provides one stage of auxiliary heat for IDUs
- Compatible LG Gen 2 Multi V indoor units: High Static Ducted, Low Static Ducted, 1Way Ceiling Cassette, 2Way Ceiling Cassette, 4Way Ceiling Cassette, and Ceiling Suspended
- Compatible LG Single Zone and Multi F indoor units: High Static Ducted, Low Static Ducted, Console, Cassette, Vertical AHU

#### Notes:

1. If a Third-Party Dry Contact and an LG internal heater or an LG Auxiliary Heater Kit is installed, supplemental heat capability cannot be controlled by the Third-Party Thermostat.
2. Must follow installation instructions in the applicable LG installation manual.

