Job Name/Location: Tag #:

For: File Resubmit
Approval Other
GC:
Mech:

Rep:

(Company) (Project Manager)

PREMTA000

LG Premium Wired Remote Controller

Electrical:

Power Supply	Powered from indoor unit
--------------	--------------------------

Surrounding Conditions:

Operating Temperature	32-104 °F
Storage Temperature	-4-176 °F
Humidity	0-90% (non-condensing)

Unit Data:

Dimensions	5-1/2" W x 4-3/4" H x 3	3/4" D
Maximum Number of Indoor Units	(per controller)	16
Maximum Number of Controllers (per group)	2

Standard Features:

- •4-1/4" Backlit LCD
- Clock
- Screensaver

Basic Functions:

- •Room temperature display
- •Operation On/Off
- •Mode Auto/Cool/Dry/Heat/Fan Only (for AC unit)
- •Ventilation mode (for ventilator unit)
- Occupied cooling and heating temperature setpoints
- Unoccupied cooling and heating setback temperature setpoints
- •Fan speed Auto/Low/Med/High/Power
- Discharge vanes Auto/Swing/Fixed¹
- Controller lock function
- •Static pressure installer setting
- Function setting for plasma filter, electric heat, humidifier, elevation grille, ventilation kit, and auxiliary heat option
- Error code display during unit or system malfunction
- Auto restart on power failure

Advanced Functions:

- •Time of day scheduling, 5 events per day with control of occ/unocc, on/off, mode, setpoints, and fan speed
- Two setpoint autochangeover
- •Minimum difference between setpoints (1-7°F) adjustable deadband
- Setback function
- •Time overide function
- •Check energy usage display
- Target energy consumption display
- •Time limit control
- Hold function
- Setpoint range lock






Connectivity:

LG Communications	1 Channel/RS-485 V-Net
La Communications	I Chamilely NO 400 V NCt

Communications Cabling Specifications (V-Net):

Тур	Field Supplied
Size	22-3 AWG, twisted, stranded, unshielded
Ler	th ² 164 ft

AWG - American Wire Gauge



- Operational indication touchscreen
- Sub function button
- Back button
- Home button

Settings button

Energy Savings button

- Schedule button
- 5 On/Off button

Notes:

- 1. Available functions/features may differ based on connected system.
- Communication cable can be extended to a maximum of 164 feet by using field supplied wire or the Wired Remote Group Control Cable Assembly (PZCWRCG3) or Wired Remote Extension Cable (PZWRC1), maximum of 4.
- 3. Must follow installation instructions in the applicable LG installation manual.

Optional Accessories (sold separately):

- PZCWRC1 33-foot Extension Cable Assembly
- PZCWRCG3 Group Control Cable Kit
- PQWRHQOFDB Wireless Remote Controller